

568 EX

CERTIFICATION

ATEX



II 2 G Ex ia IIC T4 Gb

IECEX



Ex ia IIC T4 Gb

NEC



Class I, Zone 1, AEx ia IIC T4 Gb
Class I, Zone 1, Ex ia IIC T4 Gb
Class I, Division 2, Groups A-D, T4

CERTIFICATION

PCEC



Ex ia IIC T4 Gb

INMETRO



Ex ia IIC T4 Gb

GOST



1Ex ia (op is Ga) IIC T4 Gb X

Infrared-Thermometer **FLUKE 568 EX** FOR ZONE 1

FEATURES & FUNCTIONS

- Precise measurements with accuracy
- Easily measure hard-to-reach objects
- Measurements from Zone 1 into Zone 0
- Measurements of moving materials
- Easy emissivity adjustment
- Data logging up to 99 points
- 6 languages available

STANDARD DELIVERY

- Fluke 568 EX
- Batteries
- Leather case
- Carrying case
- Operating instructions, Safety instructions
- K-type thermocouple

APPROVALS

The Fluke 568 EX combines a large number of worldwide approvals for use in potentially explosive environments – from ATEX to IECEx and NEC – meaning that it is no longer necessary to deploy and integrate different equipment on different continents.

This makes the thermometer a perfect example of portable, intrinsically safe measuring instruments – not least of all due to the numerous features unique to measurement devices in potentially explosive areas.



FOR HARSH ENVIRONMENTS



QUICK AND EASY

This intrinsically safe Fluke 568 EX infrared thermometer is the ideal companion for taking complex measurements in hazardous areas easily and efficiently. Due to the ergonomic and rugged design, even in harsh environments the 568 Ex is the ideal device. The thermometer can be used to capture and recall up to 99 values at one time. The adjustable emissivity feature allows you to take readings from a range of different materials during your round thanks to the integrated material table.

TECHNICAL DATA

Infrared temperature range	-40 °C...+800 °C (-104 °F...+1472 °F)
Display resolution	0.1 °C / 0.1 °F
Infrared response time	<500 ms
Distance to measurement spot size (D:S)	50:1
Storage	Up to 99 points with time and date
Min/Max/Avg/Dif	Yes
Emissivity adjustment	Digitally from 0.1 to 1.00 by 0.01
Accuracy	>0 °C +-1 °C or 1 %, whichever is greater
Laser sighting	Single-point laser
Ambient temperature	0 °C ... +50 °C (+32°F ... +122°F)
Power supply	2x AAA, type approved
Battery life	4 h continuous operation
Weight	Approx. 365 g (12.87 oz)

ACCESSORIES

ARTICLE NO.	PRODUCT DESCRIPTION	
A0001160	WKS-Calibration	
A0001161	DAkkS-Calibration	
A0001162	Leather case LH568	

EMEA

Germany (Headquarters) ¹

ecom instruments GmbH
Industriestraße 2
97959 Assamstadt
Phone +49 62 94 42 24-0
Fax +49 62 94 42 24-100
sales@ecom-ex.com

¹ also responsible for Austria

Benelux ²

ecom instruments BV
Watertoren 45c
3247 CL Dirksland, Netherlands
Phone +31 1 87 60 59 16
Fax +31 1 87 60 33 47
info.nl@ecom-ex.com

² also responsible for Belgium and Luxembourg

France ³

ecom Nied sarl
4 Rue Ettore Bugatti
67201 Eckbolsheim
Phone +33 3 88 76 46 84
Fax +33 3 88 76 02 85
info.fr@ecom-ex.com

³ also responsible for Algeria, Egypt, Morocco, Libya and Tunisia

Italy

ecom instruments srl
Via Gandhi, 15 Galleria
20017 Rho (MI)
Phone +39 02 93 90 92 16
Fax +39 02 93 90 62 97
info.it@ecom-ex.com

Switzerland

ecom instruments GmbH
Merkurstraße 2
6210 Sursee
Phone +41 4 19 21 60 00
Fax +41 4 19 22 00 08
info.ch@ecom-ex.com

United Kingdom

ecom instruments ltd
A310, The Wilton Centre,
Redcar, TS10 4RF
United Kingdom
Phone +44 1642 46 54 00
Fax +44 1642 46 54 02
info.uk@ecom-ex.com

Nordics

ecom instruments GmbH
Postbox 304
2970 Hørsholm
Denmark
Phone +45 28 252 575
info.nordics@ecom-ex.com

Middle East

ecom instruments fze
P.O. Box 8918
Saif-Zone, Sharjah, UAE
Phone +971 6 5 57 34 30
Fax +971 6 5 57 34 31
info.uae@ecom-ex.com

Americas

USA

ecom instruments Inc.
1779 Westborough Drive, Suite 102
Katy, Texas 77449
Phone +1 281 496 59 30
Fax +1 281 496 23 21
sales.us@ecom-ex.com

Asia

South East Asia

Ecom Instruments (SEA) Pte Ltd
15 Pioneer Turn
P+F GDC Building
Singapore 627577
Phone +65 6779 9078
info.sg@ecom-ex.com



Find your local ecom partner at www.ecom-ex.com